



SALES ORDER ACKNOWLEDGEMENT

REV4

Chrysler Group LLC - USA
3280 South Clement Avenue
Milwaukee, WI 53207-2838

Phone: 586-497-1302
Fax: 586-497-0604
Quote: 40363D

Attn: Dana Zeigler
Email:
Shipping:

(34) THIRTY-FOUR 2014 TJ5000DR OFF-HIGHWAY TRAILER JOCKEY Terminal Tractor equipped as follows:

ENGINE: Cummins QSBT4i @ 164 HP, w/CAC

TRANSMISSION: Allison RDS-3500 Electronic Transmission

FRONT AXLE: Meritor FF-961; 12,000 lb. Capacity w/ Stemco w/o ABS w/ Haldex Slacks

STEERING: TAS-65 Power Steering

REAR AXLE: Meritor RS24-160; 7.17:1 Ratio; 30,000 lb. Terminal Rating w/ Haldex Slacks

SUSPENSION: Dura-Ride

WHEELBASE: 116", 82" Between Cab and Center 5th Wheel in Up Position and Cab

FIFTH WHEEL: Holland Hitch, FW35 – 70,000 lb. Capacity

LIFT CYLINDERS: 5" Diameter, 70,000 lb. Lift Capacity, 16" Lift Height

TIRES & WHEELS: Goodyear G399 295/75R22.5 – Front & Rear Hub Piloted Wheels

EXHAUST: Vertical w/Heat Shield

PAINT: Cab & Platform- Chrysler Grey; Frame-Black; Bumper-Black; Wheels-Chrysler Grey (Dupont GMA-6281M)

All Steps, Handrails & Grating – Safety Yellow

STANDARD FEATURES:

Vista Extended Height Comfort Cab w/ Side Door
Translucent Sun Visor
60/40 Slider Glass
Cab Undercoating
4 Point Air Ride Cab
Extended Life Coolant
Coolant Recovery Bottle
8" Convex Mirrors
Back-up Alarm
Windshield Washer w/Electric Intermittent Windshield Wipers
Door Locks
Five Top-of-Cab Clearance Lights – LED
Silicone Hoses
Air Intake Mounted Restriction Gauge
45,000 BTU Heater/Defroster
Gauge Package: Volt Meter, Oil Pressure, Water Temperature, Fuel Level (Not Available in CNG or LNG), Air Pressure, Hour Meter, Speedometer & Odometer
Warning Devices: High Beam Headlight Indicator, Turn Signal-hazard Flasher Indicator, Low Fuel and Low Air Pressure Light & Buzzer, Light and Buzzer for Engine Oil Pressure
50 degree Taper Curb Side Deck and Bumper
Air Tank Pull Cords, (All)
Bendix ADIP Air Dryer
Front & Rear Tow Hooks
10 Year Frame Warranty

FUEL TANK:

50 Gallon Round Fuel Tank, Curbside
Step-Style Battery Box

THE EQUIPMENT HEREIN IS FOR OFF-ROAD PURPOSES AND DOES NOT MEET STANDARDS FOR STREET OPERATIONS IN COMPLIANCE WITH E.P.A. REGULATIONS. TRACTOR SPEED IS LIMITED TO 25 M.P.H.

ADDITIONAL FEATURES INCLUDED IN QUOTED PRICE:

Stemco Seals & Caps
(2) Power Terminals Behind Dash to accommodate Computer and Two-Way Radio
AM/FM/CD Player, MP3 Input w/ Speakers
Fire Extinguisher, 5 lb.

Air Horn
 Air Intake Filter Minder Dash Mounted
 Trailer Air Hoses, 16' Straight
 Trailer Electric Cable, 15' Straight
 Heavy Duty Formed Cab Guards with Toe Guards
 Flexible Rear Fenders
 Front Tire Flaps, Behind Front Tires
 Rear Tire Flaps, Behind Rear Tires
 Rear Tire Flaps, In Front of Rear Tires
 Graco Auto-Lube System
 (3) Group 31, 1000 CCA Maintenance Free Batteries
 Spin Air Pre-Cleaner
 Block Heater
 Fan Clutch
 Air Conditioning
 360 Degree Spotlight
 Rear Facing Work Light, Driver Side Roof Mount - Incandescent
 Rear Facing Work Light, Curb Side Mirror Post Mount - Incandescent
 (2) Forward Facing Work Lights, Roof Mounted - Incandescent
 Forward Facing Work Lights on a Switch
 Amber Strobe Light Wired Through Ignition Switch
 Break-Away Brackets for Rear-Facing Work Lights
 Heated Mirrors w/ Right Side Motorized
 Lever Shift Transmission Selector
 Flaming River Battery Disconnect w/ Lockout
 Magnetic Drain Plug
 Haldex Slack Adjusters, Front & Rear
 Grid Heater
 Robust Seat Specifically Designed by CVG Seating, Inc Positioned 1" Back On Slider
 Noise Level Less Than 80 DB at Top Gear
 No Glass Behind Driver Seat
 Insulation Behind Driver Seat
 T-Valve w/ Schrader (Air Hose Hook-up)
 Panhead Bolts on Platform
 Toe Guard at Rear Door
 45 Degree Fitting for Air Supply to Trailer w/ Quick Disconnect Couplers
 Anti-Skid Tape on Top of Frame Rails, Battery Box, and Top Deck Flat Surfaces
 Modified Rear Frame Rail Extension
 Trucklite Brand Backup, Stop, Tail, Turn Signals - LED
 Fuel Tank Mounted Curb Side
 Hydraulic System w/ Constant Running Wet Spline PTO
 Road Speed Governed to 25 MPH
 EZ Claw Hose Tender Mounted Curbside Light Bracket
 Leaf Spring Front Suspension 10x11
 Tilt & Telescopic Steering
 Cab Fan
 Anti-Spray Rain Trapper Skirting, Both Sides of Platform
 Heated 8" Convex Mirrors
 Heater Shut-Off Valve
 Three Point Orange Seat Belt

Revisions per Pilot Review 10-2-2014:

REV2

Modify rear frame ramp to have top wrapper bar follow contour of welded side plates
 Provide "ITS" style front bumper reinforcement to frame and include bumper dock rubber across front
 and sides
 Change Power Terminal to one set on back of dash on production units, pilot will be accepted with two
 sets
 Add two auxiliary power ports in dash to pilot and production units

Change mirrors to RS and LS, Heated, 4-way Moto Mirror
Reverse front air tank bolts for threads pointing inward
Move mirror post work light to standard platform mount location
Confirm Heater shut off valve plumbing is correct. If possible relocate with front grill area
Seek option for black/yellow safety stripe anti skid tape for top deck
Replace hex head screws on padded dash threshold with pan head style
Add "No Step" decal to top of hydraulic tank
Add extension to exhaust stack to get above cab roof
Change Curb Side (RS) fuel tank step to Dean Foods Style
Add 50 gallon round fuel tank to standard location on left side with Dean Foods style fuel tank step
Relocate EZ Claw to curbside light bracket
Cancel unit 25717 per Pilot

REV3